ProLite E1706S-1

The 17'' ProLite E1706S is one of the iiyama's New range of Eco Friendly products. With just a 19W typical power usage and as little as 1W in standby mode the monitor is an ideal choice for ECO-conscious consumers. By switching in the ECO Mode you can lower the power consumption even more and make sure the CO2 emission into the environment is considerably reduced. The ProLite E1706S delivers a sharp 20000:1 Advanced Contrast Ratio (ACR) and includes DVI and VGA connectivity. The monitor is available in Black and White.

Panel	TN
Diagonal	17"
Display area h x w	270.3 x 337.9 mm; 10.6" x 13.3"
Response time	5 ms
Contrast	20000 : 1 ACR
Contrast	800 : 1 typical
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170°/155°; right/left: 85°/85°; up/down: 75°/80°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
Synchronization	Separate Sync
Speakers	2 x 1 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, DVI-D Cable, Audio cable, user manual, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, RU, JP, Chinese) and 5 front controls (Power, Menu/ Select Button, +/ Volume Button (+), -/ ECO Button (-), AUTO)
User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position), colour adjust (gamma, colour temperature), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, information), volume, auto adjust
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	Energy Star®
Safety	CE, TÜV-GS, VCCI-B, TCO '03
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	20 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	371.5 x 382.5 x 190 mm
Weight	3.6 kg
Aspect ratio	5 : 4

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.